

# SLH RANGE

## SUSPENDED LED HIGH BAY PENDANT



SLH/CL

The SLH range has been introduced as an LED alternative to our SHP range.

This LED range has been built to incorporate the Philips DLM light engine and coupled with the Lexalite refractor it achieves a high DLOR of 92.5% (80% with the Opal refractor). Thermal derating ensures efficiency and long life of 60,000 hours (L70), operating temperature -25°C to +35°C.

The SLH comes with a 2m suspension kit as standard with a white body. Black and grey body options are also available

LUMINAIRE CAT NO	POWER (t€W)	COLOUR TEMP (K)	LUMEN OUTPUT*	EFFICACY LM/W	WEIGHT KG	DIM & OR EM
SLH110/3000	11.0	3,000	955	86.5	1.8	●
SLH110/4000	11.2	4,000	1,037	94.9	1.8	●
SLH200/3000	20.6	3,000	1,871	90.8	1.8	●
SLH200/4000	20.6	4,000	2,032	98.7	1.8	●
SLH300/3000	30.1	3,000	2,847	94.6	1.8	●
SLH300/4000	30.0	4,000	3,088	103.0	1.8	●
SLH500/3000	48.5	3,000	4,465	92.0	1.8	●
SLH500/4000	48.6	4,000	4,844	99.6	1.8	●

\*Lumen output of the luminaire on a 25°C ambient temperature (operating temperature: -20°C to 35°C)

### ADDITIONAL ORDERING INFORMATION

- |                           |             |                |                    |
|---------------------------|-------------|----------------|--------------------|
| • Mains Dimming           | – add /MDIM | Body finishes: |                    |
| • DALI Dimming            | – add /DALI | • White Body   | – add /as standard |
| • Optical reflector       | – add /OP   | • Black Body   | – add /B           |
| • Conical lens            | – add /CL   | • Grey Body    | – add /G           |
| • 5m suspension kit       | – add /5M   |                |                    |
| • EM version (not SLH500) | – add /EM   |                |                    |

LED colours :

- Warm white (3,000K)
- Cool white (4,000K)

### FEATURES

- Incorporates Philips DLM light engine
- Polycarbonate Lexalite Refractor
- DLOR 92.5%
- 60,000 Hours - L70 B10
- CRI 80
- DALI compatible
- Mains dimming option
- Opal refractor option
- Conical Lens accessory option
- 2M Suspension kit as standard (5m option available)
- Class II SELV

### DIMENSIONS

