

TLL RANGE

BACK LIT METAL PAN MODULAR



The TLL is a high quality back lit recessed luminaire designed to fit most metal pan ceilings or exposed grid ceilings where a high lumen output is required. It comes supplied with a polar frost diffuser as standard, but for low glare usage the TLL can be supplied with a UGR<19 diffuser.

To further increase its flexibility the TLL range can also be supplied to fit plasterboard ceilings and comes with the option for DALI dimming.

The TLL is available as an emergency fitting supplied integrally through the LED boards.

LUMINAIRE CAT NO	NOMINAL SIZE MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KG	DIM OPT	EM OPT
TLL500/150	500x500	3,629	29.9	4.25	•	•
TLL500/150(HO)	500x500	4,496	39.2	4.25	•	•
TLL600/225	584x584	3,570	28.0	5.1	•	•
TLL600/225(HO)	584x584	5,950	51.5	5.1	•	•

*The lumen output of the luminaire based on 4,000K LED diodes

ADDITIONAL ORDERING INFORMATION

- DALI dimming - add /DALI
- Recessed Tee ceiling - add /R
- Plasterboard ceiling - add /PB
- Emergency version - add /EM
- Ra>90 - add /Ra90
- UGR <19 Diffuser - add /UGR

- LED Colours:
- Warm White (3000k) - add /CLWW
 - Cool White (4000k) - add /CLCW
 - Daylight White (6500k) - add /CLDW

- Body Colours
- White as standard

FEATURES

- Ra 80 as standard
- Ra >90 version available
- 3,000K/ 4,000K/ 6,500K colour options
- Supplied to fit metal pan ceilings
- Can also be supplied to fit plasterboard or exposed tee 15 and 24mm ceiling
- DALI dimming option
- UGR <19 diffuser option
- Integral emergency version.
- Alternative sizes are available on request

DIMENSIONS

