

PDL RANGE

IDEAL FOR SCHOOLS AND HEALTHCARE APPLICATIONS



This surface mounted luminaire is ideal for educational and healthcare applications either as standalone units or continuously mounted providing both downward and upward light.

The fitting is supplied with an LED optimized PMMA diffuser which offers excellent light control. The moulded polycarbonate end caps which retain the diffuser are secured with tamperproof fixings for added security. The body and end caps are supplied in white only.

LUMINAIRE CAT NO	NOMINAL SIZE MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KG	DIM OPT	EM OPT
PDL430(HE)	1,183	3,435	33	3.2	•	•
PDL430	1,183	5,241	53	3.2	•	•
PDL430(HO)	1,183	7,051	80	3.2	•	•
PDL530(HE)	1,483	4,410	40	3.8	•	•
PDL530	1,483	6,552	65	3.8	•	•
PDL530(HO)	1,483	8,814	97	3.8	•	•

HO denotes high output

*The lumen output of the luminaire based on 4,000K LED diodes @25°C ambient

ADDITIONAL ORDERING INFORMATION

- DALI dimming - add /DALI
- Emergency version - add /EM
- LED Colours:
 - Warm White (3000k) - add /CLWW
 - Cool White (4000k) - add /CLCW

- Body Colours:
- White as standard

FEATURES

- Provides upward light onto the ceiling
- DALI dimming option
- Emergency integral version
- Tamperproof fixings
- CRI>80
- L80B10 @50,000hours
- Up to 113 Llm/tcW

DIMENSIONS

